ThinkCentre M720 Tiny 10T8SA3C00

Product

ThinkCentre M720 Tiny

Region

LA

Country/Region

Mexico

Machine Type

10T8

TopSeller

No

Processor

Intel Core i7-8700T (6C / 12T, 2.4 / 4.0GHz, 12MB)

Chipset

Intel B360 Chipset

Graphics

Integrated Intel UHD Graphics 630

Memory

1x 8GB DDR4-2666

Storage

1x 1TB HDD 7200rpm 2.5"

Optane Memory

None

Optical

None

Speaker

1.5Wx1

Ethernet

Integrated 100/1000M

WLAN + Bluetooth

Intel 8265 11ac, 2x2 + BT4.2

Optional Rear Ports

1x VGA + 1x Serial

Chassis Intrusion Switch

Chassis Intrusion Switch

Kensington Cable Lock

None

Adapter Cage

None

Toolless Chassis Screw

None

Dust Filter

None

VESA Mount

VESA Mount

Color

Black

Stand

None

Keyboard

USB Calliope Keyboard, Spanish (LA)

Mouse

USB Calliope Mouse

Power Supply

90W 88% Adapter

TUV Low Noise

None

Monitor Cable

None

System Management

None

Operating System

Windows 10 Pro 64, Spanish

Bundled Software

None

Base Warranty

3-year, Onsite

Bundled Service

None

EAN/UPC

193386977803

End of Support

N/A

Announce Date

2019-03-12

Recommended Services

Better

4Y Premier Support Upgrade from 3Y Onsite (5WS0T36207)

Good

3Y Premier Support Upgrade from 3Y Onsite (5WS0U26647)

WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



https://psref.lenovo.com

Visit psref website for the latest version of Product Specifications Reference.
© Lenovo, 2020. All rights reserved.



ThinkCentre M720 Tiny Platform Specifications

Processor	Intel® Celeron®, Intel Pentium®, or 8th / 9th Gen Intel Core™ i3 / i5 / i7 / i9 Processor							None				
	Processor	Cores / Threads	Frequency Base/Max(GHz)	Cache	Memory Support (Up to)	Integrated Graphics	Security chip Security features	Discrete TPM 2.0, TCG Certified Security slot (in rear for optional Boot sequence control				
	Celeron G4900T	2/2	2.9G	2 MB	DDR4-2400	UHD 610		Kensington® MicroSaver® cable) ● Boot without keyboard and mo			yboard and mouse	
	Pentium Gold G5400T	2/4	3.1G	4 MB	DDR4-2400	UHD 610		 Chassis intrusion switch Power-on password Individual USB port disablement Smart USB protection, allows 		ection allows keyboard/		
	Pentium Gold G5500T	2/4	3.2G	4 MB	DDR4-2400	UHD 630	1	Administrator passion	word	mouse only. bloc	cks all storage devices	
	Core i3-8100T	4/4	3.1G	6 MB	DDR4-2400	UHD 630		Hard disk password	<u>d</u>			
	Core i3-8300T	4/4	3.2G	8 MB	DDR4-2400	UHD 630		Some: Lenovo Calliope Keyboard (USB connector), black				
	Core i5-8400T	6/6	1.7G / 3.3G	9 MB	DDR4-2666	UHD 630		Some: Lenovo Tradit	vo Traditional Keyboard (USB connector), black		ick	
	Core i5-8500T	6/6	2.1G / 3.5G	9 MB	DDR4-2666	UHD 630	Mouse	Some: Lenovo Callic	Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, bla Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black			
	Core i5-8600T	6/6	2.3G / 3.7G	9 MB	DDR4-2666	UHD 630		Some: Lenovo Callic				
	Core i7-8700T	6/12	2.4G / 4.0G	12 MB	DDR4-2666	UHD 630		Some: Lenovo Callic				
	Core i3-9100T	4/4	3.1G / 3.7G	6 MB	DDR4-2400	UHD 630		Tiny (1L), black color	<u>'</u>		· · · · · · · · · · · · · · · · · · ·	
	Core i3-9300T	4/4	3.2G / 3.8G	8 MB	DDR4-2400	UHD 630		 Toolless chassis op 	en (need optional	I toolless chassis so	rew)	
	Core i5-9400T	6/6	1.8G / 3.4G	9 MB	DDR4-2666	UHD 630	1	 Toolless HDD, SSD), memory remova	1	•	
	Core i5-9500T	6/6	2.2G / 3.7G	9 MB	DDR4-2666	UHD 630		Optional dust filter S	Optional dust filter one 2.5" bay for HDD/SSD, one PCIe 3.0 x8 slot (low-profile), two M.2 slot or WLAN, one for M.2 SSD), 2.5" HDD/SSD and PCIe card are mutually e		lo) two M O alata /	
	Core i5-9600T	6/6	2.3G / 3.9G	9 MB	DDR4-2666	UHD 630		for WLAN, one for M			nej, two ivi.2 Siots (one d are mutually exclusive	
	Core i7-9700T Core i9-9900T	8/8 8/16	2.0G / 4.3G 2.1G / 4.4G	12 MB 16 MB	DDR4-2666 DDR4-2666	UHD 630 UHD 630		, OHO IOI IVI.	· · · · · · · · · · · · · · · · · · ·			
						חנים חווי	1	Time and		ns (WxDxH)	Weight (Approx.)	
Memory	32GB max, DDR4-266 dual-channel capable	•	·			_		Tiny only	179mm X 182.9	20" X 1.36" 9mm X 34.5mm	2.91 lb (1.32 kg), vary by config	
Storage	* System automatically Some: Hard Drive / S		<u> </u>			ry controller	[With VESA mount & ODD box		30" X 2.48" 5.38mm X 63mm	3.66 lb (1.66 kg), vary by config	
2 	Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Some: M.2 SSD / PCIe NVMe, PCIe 3.0 x 4*, 32Gb/s * 128GB SSD M.2 (2242) PCIe NVMe only supports PCIe 3.0 x 2, 16Gb/s Some: Intel Optane™ Memory (not support Celeron / Pentium Processor), M.2 Some: DVD-ROM, slim (9.0mm), via USB external ODD box Some: DVD Burner (DVD±RW), slim (9.0mm), via USB external ODD box						VESA mount Floor Stand	Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation				
Optical							Power supply	Some: 65 watts AC/DC adapter, autosensing, 88% PSU Some: 90 watts AC/DC adapter, autosensing, 88% PSU Some: 135 watts AC/DC adapter, autosensing, 88% PSU				
Onboard SATA	One onboard SATA 6.0Gb/s connector						Limited warranty	1 , 3,				
Graphics	Intel HD Graphics 610/630 in processor, uses main memory, DirectX [®] 12, one DisplayPort™, one HDMI, one optional video port (2nd HDMI, VGA, 2nd DP, or USB 3.1 Type-C Gen1 with DisplayPort function), up to 3 independent displays; <i>Max resolution:</i> 4096x2304 (DP) @ 60Hz; 4096x2304 (Type-C) @ 60Hz;						,	Some: 1-year or 3-year, limited onsite service / service upgrades available				
							Preload Preloaded operating system Some: Windows® 10 Pro 64-bit					
	### ##################################					₹50Hz		Some: Windows 10				
Monitor cable	Optional DP to VGA dongle, DP to DVI-D dongle, DP to dual DP dongle (for Collage Display with intel integrated graphics), or DP to HDMI 1.4 dongle							Preloaded applications (only some listed) Lenovo Vantage				
Chipset	Intel B360 Chipset						1	Microsoft Office pre				
Front ports* (Std.) one USB 3.1 Gen1 (Always On and fast charge), one USB 3.1 Type-C Gen 1,								 purchase a product key to activate Cyberlink PowerDVD (only for models with DVD / DVD±RW) 				
Rear ports* (Std.)	-ront ports" (Std.) one USB 3.1 Gen I (Always On and tast charge), one USB 3.1 Type-C Gen I, one microphone (3.5mm), one headphone / microphone combo jack (3.5mm) Rear ports* (Std.) 2x USB 3.1 Gen2, 2x USB 3.1 Gen1, 1x ethernet (RJ-45), 1x DisplayPort, 1x HDMI							Cyberlink PowerDVD (only for models with DVD / DVD±RW) Cyberlink Power2GO (only for models with DVD±RW) LinkedIn				
	Rear ports* (Opt.) Two optional ports (mutually exclusive with PCIe card): Port 1 for VGA / 2nd DP / 2nd HDMI / serial / USB 3.1 Type-C Gen 1 with DP function); Port 2 for serial;							ENERGY STAR® 7.0, EPEAT™ Gold rating (North America), ErP Lot 3, TCO, TUV ultra low noise verified (coming soon, on some models), RoHS-compliant				
	Optional ports via PCI PCIe x1	e card: 2.	card: 2x USB 3.1 Gen1 via PCle x1, 4x serial (9-pin) via					MIL-STD-810G milita	ary certification (Lo	ow Pressure [Altitud	Pressure [Altitude], High Temperature,	
	* Depending on many factors, actual data transfer speed may be lower than theoretical speed						Low Temperature, Ter	mperature Shock,		d Dust, Vibration, Shock,		
Audio support	Realtek ALC233VB2 /	ALC233VB2 / optional internal speaker (1.5 watt or 2 watt)					Fungus, Solar Radiation)					
WLAN	Some: 11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 1x1						Accessories	For compatible accessories, please go to http://smartfind.lenovo.com				
	Some: 11ac wireless, Wi-Fi + Blueto	Some: 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2										
	Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.2 combo adapter, 1x1											
	Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2											
Bluetooth	Wi-Fi + Blueto Some: Bluetooth 4.2				`combo adaptor							
Ethernet (Opt.)	Gigabit ethernet, Intel Some: Intel Ethernet S	Ethernet	Connection I219	9-V (Jac	cksonville), Wake							
,	ations above may not be			, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		, . JIJ AT					Lanava Juna 2010	











