ThinkCentre M630e Tiny Platform Specifications

Processor	Intel® Pentium®, or 8th Generation Intel Core™ i3 / i5 Processor						Manageability	None				
	Processor	Cores / Threads	Frequency Base/Max(GHz)	Cache	Memory Support	Integrated Graphics	Security chip	rity chip Firmware TPM 2.0, integrated in chipset rity features Security slot (in rear for optional Kensington® MicroSaver® cable) Boot sequence control Boot without keyboard and mouse				
	Pentium Gold 5405U	2/4	2.3G	2 MB	(Up to) DDR4-2133	UHD 610	Security leatures					
	Core i3-8145U	2/4	2.1G / 3.9G	4 MB	DDR4-2400	UHD 620		Chassis intrusion switch Individual USB port disablement				
	Core i5-8265U	4/8	1.6G / 3.9G	6 MB	DDR4-2400	UHD 620		Power-on password Smart USB protection, Administrator password				
Memory	16GB max, DDR4-2666*, one 260-pin SO-DIMM sockets, non-ECC * System automatically clocks down for the processors with lower memory controller							Administrator password mouse only, blocks all storage devices Hard disk password Company Collispo Keyboard (USP connector), block				
Storage	Some: Hard Drive / SATA 6.0Gb/s, 2.5", 5400 rpm or 7200 rpm						Keyboard Mouse	Some: Lenovo Calliope Keyboard (USB connector), black Some: Lenovo Calliope Mouse (USB connector), black				
Onboard SATA	Come. Calld Diver Diver (COD) / CATA COOK to Coll						Mechanical	Tiny (1L), black color; metal case Optional dust filter One 2.5" bay for HDD/SSD, two M.2 slots (one for WLAN, one for M.2 SSD)				
Graphics	Intel HD Graphics 610/620 in processor, uses main memory, DirectX [®] 12, one DisplayPort™, one HDMI, up to 2 independent displays; Max resolution: 4096x2304 (DP) @ 60Hz; 4096x2304 (HDMI) @ 24Hz						†		Dimension	ns (WxDxH)	Weight (Approx.)	
·								Tiny only		20" X 1.36" 9mm X 34.5mm	2.91 lb (1.32 kg), vary by config	
Monitor cable	Optional DP to VGA dongle or DP to HDMI 1.4 dongle						VESA mount	Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation				
Chipset	Intel SoC (System on Chip) platform						Floor Stand					
Front ports* (Std.)	td.) One USB 3.1 Gen1, one USB 3.1 Type-C Gen 1, one microphone (3.5mm),						Power supply	Some: 65 watts adapter, autosensing, 88% PSU				
one headphone / microphone combo jack (3.5mm) Rear ports* (Std.) Two USB 3.1 Gen1, two USB 2.0, one ethernet (RJ-45), one DisplayPort, one HDM Rear ports* (Opt.) None						Limited warranty	Some: 1-year, depot service / service upgrades available Some: 1-year, limited onsite service / service upgrades available					
	* Depending on many factors, actual data transfer speed may be lower than theoretical speed Realtek ALC233VB / internal speaker (1.5 watt) Some: 11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2						Preload	Preloaded operating system Some: Windows® 10 Pro 64-bit Some: Windows 10 Home 64-bit Preloaded applications (only some listed) Lenovo Vantage Microsoft Office preloaded; purchase a product key to activate				
Audio support												
WLAN												
	Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165,						• LinkedIn					
	Wi-Fi + Bluetooth 4.2 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2 Some: Bluetooth 4.2 wireless, integrated in Wi-Fi + BT combo adapter Gigabit ethernet, Realtek RTL8111HN-CG None						Environment	ENERGY STAR® 7.0, EPEAT™ Silver rating, ErP Lot 3, TCO, RoHS-compliant, WEEE, REACH				
Bluetooth							MIL-SPEC test	Coming soon				
Ethernet (Opt.)							Accessories	For compatible accessories, please go to http://smartfind.lenovo.com				

Note: The specifications above may not be available in all regions.