ThinkPad T490 Platform Specifications

Processor	8th Gener	ation Ir	ntel® Co	re™	i5 / i7 Pr	ocessor					Dimensions	<i>WxDxH:</i> 12.95" x 8.94" x 0.70"; 329mm x 227mm x 17.9mm					
	Processor # of Number Cores		# of			Max Turbo C	ache	Memory	Processor Graphics		Weight	Models	HD	FHD	FHD Low Power / WQHD	· · · · · · · · · · · · · · · · · · ·	
	i5-8265U	Cores 4	Threads I	+	equency 6 GHz	3.9 GHz 6	6MB	Types	Graphics		Case color Case material	Weight Black	3.37 lb / 1.53 kg	3.41 lb / 1.55 kg	3.23 lb / 1.46 kg	3.56 lb / 1.61 kg	
	i5-8365U				6 GHz				Intel UHD Graphics 620	Display cover: PPS / 50% GF;							
	i7-8565U			_	8 GHz		MB	DDR4-2400				Bottom: PA / 50% GF					
	i7-8665U		<u> </u>						Smart card reade		rOptional: Smart card reader						
	or 10th Generation Intel Core i5 / i7 Processor (NOT available in EME										Ports	MicroSD card reader Two USB 3.1 Gen 1 (one Always On),					
			# of Threads	Fre	equency	Frequency	Cache	Memory Types	Processo Graphic			one USB 3.1 Type-C Gen 1 (with the function of Power Delivery and DisplayPort) one USB 3.1 Type-C Gen 2 / Thunderbolt 3 (with the function of PD and DP),					
	i5-10210U i7-10510U	5-10210U 4 8 1.6 GHz 4.2 GHz 6MB DDR4-2400 Intel UHD Graphics HDMI 1.4b, Ethernet (RJ-45), nano-SIM card headphone / microphone combo jack, optiona micros Decard reader side decking connector.								ional smart card reader.	, ,						
Graphics	Intel UHD Graphics 620 or Intel UHD Graphics in processor only or Intel UHD Graphics 620 or Intel UHD Graphics in processor and NVIDIA® GeForce® MX250, 2GB GDDR5 memory;										Monitor cable (optional)	HDMI to USB-C to	microSD card reader, side docking connector, security keyhole * Depending on many factors, actual data transfer speed may be lower than theoretical speed HDMI to VGA: Lenovo HDMI to VGA Monitor Adapter USB-C to VGA: Lenovo USB-C to VGA Adapter				
	supports external digital monitor via HDMI or Thunderbolt; supports three independent displays;											USB-C to HDMI: Lenovo USB-C to HDMI Adapter					
	Max resolution: 4096x2304@60Hz (Thunderbolt); 4096x2160@24Hz (HDMI)										Bundled Accy	USB-C to DP: Lenovo USB-C to DisplayPort Adapter None					
Chipset	Intel SoC					,	-		,		Camera (optional	onal) One of the following, configurable by model:					
Memory	48GB max / 2400MHz DDR4, dual-channel capable, 8GB or 16GB memory soldered to systemboard, one DDR4 SO-DIMM socket										, ,	• HD720	 HD720p camera with ThinkShutter camera privacy, fixed focus 				
						ıt run at 2400l				Kei	Audio support		IR camera and HD720p camera with ThinkShutter camera pr D Audio, Realtek® ALC3287 codec /		inkSnutter camera privac	cy, fixed focus	
Display	Size Reso	lution	-	Гуре				ct Contras		Viewing	į	stereo speakers, 2W x 2, Dolby® Audio™ Premium / optional dual array far-field microphone, headphone / microphone combo jack				combo jack	
	14.0" HD (1366x768)				Anti-glare		Ratio		Gamu 45%	t Angle 90°	 Keyboard	6-row, spill-resistant, multimedia Fn keys, optional LED backlight					
	14.0 110 (14.0 [1D (1300x700)		IIN	Ailli-giaie	250 nits	10.9	400.1	45/6	90	UltraNav™		TrackPoint® pointing device and buttonless Mylar surface multi-touch touchpad				
	14.0" FHD (1920x1080) 14.0" FHD (1920x1080) Low Power			IPS	Anti-glare	/ A I- \	16:9	700:1	45%	170°	Security Security chip	Power-on password, hard disk password, supervisor password, se Discrete TPM 2.0, TCG Certified Intel vPro Technology			curity keyhole		
				IPS	Anti-glare					: Touch style ma	style match on chip fingerprint reader on the palm rest						
	FHD (1920x1080) 14.0" ThinkPad Privacy Guard		1080) ivacy	IPS Anti-glar		e 400 nits	16:9	1000:1	1009/	170°	Battery	Integrated Li-ion 50Wh battery, supports Rapid Charge (charge up to 80% in 1hr with 65W AC adapter					
	14.0" WQHD (2560x1440) HDR, Dolby Vision™			IPS	Glossy	500 nits	16:9	1500:1			Max battery life AC adapter	* Battery	MobileMark® 2014: 16.11 hr * Battery life varies significantly with settings, usage, & other factors 45W, 65W, or 65W slim USB-C AC adapter		sage, & other factors		
Multi-touch (opt)	On-cell to	uch, su	ipports ⁻	10-fir	nger ges	ture (FHD o	nly)				Preload		e following, configu	<u>.</u>			
Storage	M.2 228M.2 224Intel Op	0 SSD 2 SSD tane™	/ PCIe / PCIe Memory	NVIV NVIV v H10	1e, PCle 1e, PCle 0 with So	T available i 3.0 x 4 3.0 x 2 olid State Sto		,				 Windows® 10 Home 64 Windows 10 Pro 64 Windows 10 Pro in S mode No OS 					
Optical	None	M.2 2280, PCIe NVMe 3.0 x 4 None									Limited warranty		e following, configui				
Ethernet	Non-vPro model: Intel Ethernet Connection I219-V (Jacksonville) vPro model: Intel Ethernet Connection I219-LM (Jacksonville)										(optional)	 1-year depot repair service 1-year depot with 2-year system board repair service 3-year/1-yr battery depot repair service 					
WLAN +	One of the following, configurable by model:]	• 1-year + 2-year/1-yr battery limited onsite service					
Bluetooth™ (optional)	 Intel Wireless-AC 9560, Wi-Fi 2x2 802.11ac + Bluetooth 5.0 Intel Wi-Fi 6 AX201, Wi-Fi 2x2 802.11ax + Bluetooth 5.0 										Mil Coop toot	3-ýear/1-yr batterý limited onsite service MIL-STD-810G military testing					
(optional)	(AX201						oour.	5.0			Mil-Spec test				IC compliant		
WWAN (optional)	One of the	following	g, configu	ırable		, ,					Environment	CPEAI'''	Silver; ENERGY	1 3 IAR" /.1; H0	no-compliant		
, , ,	WirelessIntegrateIntegrate	WAN ed Mob ed Mob	upgrada ile Broa ile Broa	ıble dbar dbar	nd 4G LT nd 4G LT	E, Fibocom	m L8	50-GL, M.2	card								
SIM card (opt)	• Integrated Mobile Broadband 4G LTE-A, Fibocom L860-GL, MIMO 4x4, M.2 card * For non-WWAN model, it means the model is NOT WWAN upgradable Nano-SIM card slot, optional Verizon LTE (US) SIM card																
					le in all r		ıvı cal	ıu								I eno	