Lenovo V330-14ARR Platform Specifications

Processor	AMD Ryzer	n™ Mo	obile Pro	cessors v	vith Radeo	n Veg	a Graphics		Dimensions	<i>WxDxH:</i> 13.5" x 9.72" x 0.79"; 343mm x 247mm x 20.3mm						
	Processor		# of	Base	Max Turbo Frequency	Cache	Memory	Processor	Weight	Models		Mi	in Ma	x w/o 2nd battery	Max w/ 2nd	battery
	Number	Cores	Threads	Frequency	Frequency	Oacrie	Туре	Graphics		Weights		1.55 kg /	3.42 lb	1.70 kg / 3.75 lb	1.85 kg / 4	.07 lb
	Ryzen 3	2	4	2.5 GHz	3.4 GHz	1MB		AMD Radeon Vega 3	Case color	Iron Grey						
	2200U							Graphics		PC/ABS p						
	Ryzen 3							AMD Radeon	Media reader Ports	4-in-1 read	der (MIV	1C, SD, SD	HC, SDXC	;) : On) one USB 3	1 Type-C Ger	
	2300U	4	4	2.0 GHz	3.4 GHz	2MB	DDR4-2400	Vega 6	TOILS	Two USB 3.0 (one with optional Always On), one USB 3.1 one USB 2.0 in Ultra-bay, VGA, HDMI, Ethernet (RJ-45)				1		
							1	Graphics AMD Radeon		* Depending on many factors, actual data transfer speed may be lower than theoretical speed.						
	Ryzen 5	4	8	2.0 GHz	3.6 GHz	2MB		Vega 8	Camera (optional)							
	2500U							Graphics	Audio support	Stereo speakers with Dolby® Audio™, 2W x 2 / optional monaural digital microphone, combo audio/microphone jack						
Graphics	AMD Radeon Vega 3 / Vega 6 / Vega 8 Graphics in processor only, or AMD Radeon Vega 3 Graphics and AMD Radeon 540 (2GB GDDR5 memory);								 Kevboard	6-row, multimedia Fn keys, spill resistant, optional backlit						
									Touchpad	One-piece touchpad, multi-touch						
	AMD Rade supports th								Security	Power-on password, hard disk password, supervisor password, security keyhole						
						1920x	1200@60Hz	(VGA)	Security chip	Firmware TPM 2.0, integrated in chipset						
Chipset	AMD SoC (System on Chip) platform							Fingerprint reader Optional: Touch style fingerprint reader on the palm rest								
Memory	8GB max / 2400MHz DDR4, dual-channel capable.								Internal battery UltraBay battery Max battery life	Integrated Li-Polymer 2-cell (30Wh or 39Wh) Optional: Li-Polymer 2-cell (39Wh)						
	up to 4GB memory soldered to systemboard, one DDR4 SO-DIMM socket									,			<u> </u>	2-cell 30Wh +	2-cell 39Wh +	ı
Display	* System clocks down for processors with lower memory controller Display Some: 14.0" (355mm) HD (1366x768), anti-glare, LED backlight,									Models	2	2-cell 30Wh	2-cell 39W	h 2-cell 39Wh	2-cell 39Wh	
Display				ect ratio	00), anii-g	iaie, L	ED Dackligh	ι,	AC adapter	Max battery	y life	5 hr	6.5 hr	11.5 hr	13 hr	
	Some: 14.0	0" (355	5mm) FH	HD (1920)	(1080), an	ti-glare	, LED backli	ght,		* Battery life varies significantly with settings, usage, & other factors.						
Multi-touch	220 nits, 16:9 aspect ratio None								AC adapter	45W or 65W AC adapter						
		D / CA	TA 6 00	h/o 0 E" v	uida 7mm	hiah			Preload	Some: Windows 10 Home 64 Some: Windows 10 Pro 64 • Lenovo Companion						
Storage	Some: SS	D/SA 2280	NA 6.0G NSSD / F	D/S, ∠.5 V PCIe NVM	vide, /mm le PCle 3	111911 0 x 2 (for Byzen 3	processor)								
	Some: M.2 2280 SSD / PCIe NVMe, PCIe 3.0 x 2 (for Ryzen 3 processor) Some: M.2 2242 SSD / PCIe NVMe, PCIe 3.0 x 2, 16Gb/s Some: M.2 2280 SSD / PCIe NVMe, PCIe 3.0 x 4 (for Ryzen 5 processor)									Lenovo Setting Microsoft Office preloaded;						
	Some: HDD / SATA 6.0Gb/s, 2.5" wide, 7mm high, optional Active Protection System (APS)									purchase a product key to activate • McAfee® LiveSafe™ (30-day trial)						
SATA controller	Serial ATA,	SATA	6.0Gb/s	support,	integrated	in pro			Limited warranty	One of the following, configurable by model: 1-year depot repair service 2-year/1-yr battery depot repair service						
UltraBay	One modul				ole devices	, botto	m access									
Ethernet	Gigabit Eth	ernet	connecti	on												
WLAN	11ac, 1x1 + BT4.1: 11ac, 1x1, Wi-Fi + Bluetooth combo adapter, M.2 Card Bluetooth 4.1 wireless, integrated in Wi-Fi + Bluetooth combo adapter								Environment	EPEAT™ Silver; ENERGY STAR® 6.1; RoHS-compliant						
Bluetooth™	Bluetooth 4	.1 wire	eiess, in	tegrated ii	n vvi-Fi + E	siuetoc	otn combo ac	apter								Lonovo