ThinkPad L490 Platform Specifications

| Processor | Intel® Celeron® Processor or 8th Generation Intel Core™ i3 / i5 / i7 Processor | | | | | | | | | Dimensions | <i>WxDxH:</i> 13.19" x 9.25" x 0.89"; 335mm x 235mm x 22.5mm |
|------------------------------|--|----------|------------|--------------------------|-------------------------------|-------|-----------------|--------------------------------|-----------------------|--|--|
| | Processor # of # of Number Cores Thread | | | Base Max Turbo Frequency | | Cache | Memory Types | | cessor phics | Weight Case color Case material | Starting at 3.72 lb / 1.69 kg Black PC/ABS plastic |
| | Cel 4305U 2 | | 2 | 2.2 GHz | - | - 2MB | | 133 Intel UHD Graphics 610 | | Smart card reader | rOptional: Smart card reader |
| | i3-8145U i5-8265U | 2 | 8 8 | 2.1 GHz 1.6 GHz | 3.9 GHz 3.9 GHz 4.1 GHz | | DDR4-2400 | Intel UHD Graphics 620 | Media reader Ports | MicroSD card reader Two USB 3.1 Gen 1 (one Always On), one USB 3.1 Type-C Gen 1 (with the function of Power Delivery and DisplayPort), one USB 3.1 Type-C Gen 2 (with the function of Power Delivery and DisplayPort), HDMI 1.4b, Ethernet (RJ-45), nano-SIM card slot (WWAN models), headphone / microphone combo jack, optional smart card reader, | |
| | i5-8365U | 4 | | 1.6 GHz | | | | | | | |
| | i7-8565U i7-8665U | 4 | 8 | 1.8 GHz 1.9 GHz | 4.6 GHz 4.8 GHz | 8MB | | | | | |
| Graphics | Intel UHD Graphics 610 or 620 in processor only or Intel UHD Graphics 620 in processor and AMD Radeon 535, 2GB GDDR5 memory (discrete models are NOT available in EMEA); supports external digital monitor via HDMI or USB Type-C; supports three independent displays; Max resolution: 4096x2304@60Hz (USB Type-C); 4096x2160@24Hz (HDMI) | | | | | | | | | (optional) Bundled Accy | microSD card reader, side docking connector, security keyhole * Depending on many factors, actual data transfer speed may be lower than theoretical speed HDMI to VGA: Lenovo HDMI to VGA Monitor Adapter USB-C to VGA: Lenovo USB-C to VGA Adapter USB-C to DP: Lenovo USB-C to DisplayPort Adapter None [a] One of the following, configurable by model: |
| Chipset Memory | Intel SoC (System on Chip) platform 64GB max / 2400MHz DDR4, dual-channel capable, two DDR4 SO-DIMM sockets * Installed memory is actually 2666MHz but run at 2133MHz or 2400MHz due to Intel limitation | | | | | | | | | HD720p camera with ThinkShutter camera privacy, fixed focus IR camera and HD720p camera with ThinkShutter camera privacy, fixed focus HD Audio, Realtek ALC3287 codec / | |
| Display | Size Resolution | | Ту | pe Surface | e Surface Brightness Aspe | | | t Color Viewing Gamut Angle | | | stereo speakers, 2W x 2, Dolby® Advanced Audio / dual array microphone, headphone / microphone combo jack |
| | 14.0" HD (14.0" FHD | <u> </u> | | N Anti-glare | | 16: | | 45% 45% | 90° 170° | Keyboard UltraNav™ | 6-row, spill-resistant, multimedia Fn keys, optional LED backlight TrackPoint® pointing device and buttonless Mylar surface multi-touch touchpad |
| | en een teuen, eupperte ne miger gestane (in 12 enny) | | | | | | | | | Security Security chip | Power-on password, hard disk password, supervisor password, security keyhole Discrete TPM 2.0, TCG Certified |
| Storage | HDD / SATA 6.0Gb/s, 2.5" wide, 7mm high, Active Protection System™ SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high M.2 2280 SSD / PCIe NVMe, PCIe 3.0 x 4 M.2 2242 SSD / PCIe NVMe, PCIe 3.0 x 2 | | | | | | | | | System Mgt (opt) Intel vPro Technology Fingerprint reader Optional: Touch style fingerprint reader on the palm rest NFC (optional) Near Field Communication | |
| Optane™ memory Optical | * Installed M.2 2280 SSD is PCle 3x4 but run at PCle 3x2 due to M.2 SSD adapter limitation by Optional: Intel Optane memory, PCle NVMe, PCle 3.0 x 2 None | | | | | | | | imitation | Battery Max battery life | Integrated Li-ion 45Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter MobileMark® 2014: 12 hr |
| Ethernet | Non-vPro model: Intel Ethernet Connection I219-V (Jacksonville) vPro model: Intel Ethernet Connection I219-LM (Jacksonville) | | | | | | | | | AC adapter | *Battery life varies significantly with settings, usage, & other factors 45W, 65W, or 65W slim USB-C AC adapter |
| WLAN + | One of the following, configurable by model: Realtek® RTL8822BE, Wi-Fi 2x2 802.11ac + Bluetooth 4.2, M.2 card (NOT available in EMEA) Intel Wireless-AC 9260, Wi-Fi 2x2 802.11ac + Bluetooth 5.0 | | | | | | | | | Operating system | Optional: Windows® 10 Home 64 or Windows 10 Pro 64 |
| Bluetooth™ (optional) | | | | | | | | | | Limited warranty | One of the following, configurable by model: 1-year depot repair service 3-year/1-yr battery depot repair service |
| VADATA NI James is a seri | Intel Wi-Fi 6 AX200, Wi-Fi 2x2 802.11ax + Bluetooth 5.0 I (optional) One of the following, configurable by model: | | | | | | | | | Mil-Spec test | MIL-STD-810G military testing |
| ., , | Wireless WAN upgradable Integrated Mobile Broadband 4G LTE, Fibocom L830-EB, M.2 card (EMEA only) Integrated Mobile Broadband 4G LTE-A, Fibocom L850-GL, M.2 card For non-WWAN model, it means the model is NOT WWAN upgradable | | | | | | | | | Environment | EPEAT™ Silver; ENERGY STAR® 7.1; RoHS-compliant |
| SIM card Note: The specifica | None | movr | not bo ava | ilablo in all r | ogione | | | | | | Lenov |

Note: The specifications above may not be available in all regions.