

## DELL S Series S2425H LED display 60.5~cm (23.8") 1920 x 1080 Pixeles Full HD LCD Negro, Plata

Marca : DELL Familia de productos: S Código del producto: S2425H

Series

## Nombre del producto:

S2425H

- 60.5cm (23.8") Full HD 1920 x 1080 Edge LED IPS
- 8ms, 16:9, 250cd/m<sup>2</sup>, 1500:1
- HDMI

Dienlay

60.5cm (23.8") Full HD 1920 x 1080 Edge LED IPS, 16:9, 250cd/m<sup>2</sup>, 16.78M, 8ms, 178°/178°, 1500:1

DELL S Series S2425H LED display 60.5 cm (23.8") 1920 x 1080 Pixeles Full HD LCD Negro, Plata:

Un monitor FHD de 24 pulgadas que optimiza la comodidad ocular y cuenta con unos impresionantes efectos visuales con una acústica excepcional en un diseño inspirado en el estilo de vida. DELL S Series S2425H. Diagonal de la pantalla: 60.5 cm (23.8"), Resolución de la pantalla: 1920 x 1080 Pixeles, Tipo HD: Full HD, Tecnología de visualización: LCD, Tiempo de respuesta: 8 ms, Relación de aspecto nativa: 16:9, Ángulo de visión, horizontal: 178°, Ángulo de visión, vertical: 178°. Altavoces incorporados. montaje VESA. Color del producto: Negro, Plata





Display		Power	
Display diagonal * Display resolution *	60.5 cm (23.8") 1920 x 1080 pixels	Energy efficiency class (SDR) * Energy consumption (SDR) per 100	D 0
HD type *	Full HD	hours *	15 KWN
Native aspect ratio *	16:9	Power consumption (typical) *	14.5 W
Display technology *	LCD	Power consumption (standby) *	0.4 W
Panel type *	IPS	Power consumption (max)	42 W
LED backlight	✓	Power consumption (off)	0.3 W
Backlight type	Edge LED	AC input voltage	100 - 240 V
Touchscreen *	×	AC input frequency	50/60 Hz
Display brightness (typical)	250 cd/m <sup>2</sup>	Input current	1.5 A
Response time *	8 ms	Power supply type	Internal
Anti-glare screen	<b>√</b>	Energy efficiency scale	A to G
Screen shape *	Flat	European Product Registry for Energy Labelling (EPREL) code	1856260
Supported video modes	480p, 576p, 1080i, 1080p	Operational conditions	
Contrast ratio (typical) * Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch	1500:1 100 Hz 178° 178° 16.78 million colours 5 ms 0.2745 x 0.2745 mm	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -20 - 60 °C 10 - 80% 5 - 90% 0 - 5000 m 5000 - 12192 m
Pixel density	93 ppi	Weight & dimensions	
Viewable size, horizontal Viewable size, vertical Surface hardness sRGB coverage (typical)	52.7 cm 29.6 cm 3H 99%	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand)	537.6 mm 163 mm 411.7 mm 3.85 kg
Performance		Width (without stand)	537.6 mm
NVIDIA G-SYNC *	×	Depth (without stand) Height (without stand)	58.9 mm 313.7 mm

Dower

Performance		Weight & dimensions	
AMD FreeSync *	×	Weight (without stand)	3.29 kg
Flicker-free technology	✓	Bezel width (side)	5.3 mm
Low Blue Light technology	✓	Bezel width (top)	5.3 mm
Multimedia		Bezel width (bottom)	1.2 cm
Number of speakers	2	Packaging data	
RMS rated power	10 W	Package weight	5.92 kg
Built-in speaker(s) *	✓	Packaging content	
Built-in camera *	x	Stand included	✓
Design		Cables included	AC, HDMI
Market positioning *	Office	Quick start guide	✓
Product colour *	Black, Silver	HDMI cable length	1.8 m
Front bezel colour	Black	Sustainability	
Feet colour	Silver	Sustainability compliance	1
Ports & interfaces		Sustainability certificates	ENERGY STAR
Built-in USB hub *	×	Doesn't contain	PVC/BFR
HDMI *	<b>✓</b>	Carbon footprint	
HDMI ports quantity	2	Total carbon footprint (kg of CO2e)	157
HDMI version	1.4	Carbon emissions, manufacturing	71
Headphone out *	×	(kg of CO2e)  Carbon emissions, logistics (kg of	
HDCP	✓	CO2e)	11
HDCP version	1.4	Carbon emissions, energy usage (kg	72
AC (power) in	✓	of CO2e) Carbon emissions, end-of-life (kg of	
Ergonomics		CO2e)	3
VESA mounting *	100 100	Total carbon emissions, w/o use phase (kg of CO2e)	85
Panel mounting interface	100 x 100 mm	PAIA version	GaBi verison1
Cable lock slot *	✓ Kensington	Other features	
Cable lock slot type  Height adjustment *	X	Compliance certificates	RoHS
Tilt adjustment	^	,	
Tilt angle range	-5 - 21°		
On Screen Display (OSD)	✓		
Plug and Play	· ·		
	-		





884116465072

0884116465072

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.